

Serial No. 10/647,786
Examiner: FLEMING, Faye M.
Art Unit 3618

Page 2 of 7

Amendments to the Specification

Please replace paragraph [0016] with the following amended paragraph:

[0016] One additional aspect of the present invention provides an ATV with a frame, and only four wheels suspended from the frame. Two of the wheels are front wheels and two of the wheels are rear wheels. The front wheels define a front axis and the rear wheels define a rear axis. The front axis and the rear axis define a wheelbase of greater than 51 inches, and each wheel includes an ATV-type tire, *i.e.* a low-pressure balloon tire having an air pressure of less than 1 kg/cm². The ATV has two shock absorbers connected to the frame. The shock absorbers are associated with the rear wheels. A power unit for driving at least one of the wheels is disposed on the frame. The ATV also has a straddle-type seat disposed on the frame, and handlebars for steering at least one of the wheels disposed on the frame.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- BLACK BORDERS**
- IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- FADED TEXT OR DRAWING**
- BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- SKEWED/SLANTED IMAGES**
- COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- GRAY SCALE DOCUMENTS**
- LINES OR MARKS ON ORIGINAL DOCUMENT**
- REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.